


## Sidewinder Jacks MINI JACKS

5-20 Ton

Compact Sidewinder Mini Jack fits in your palm and delivers 5, 10 & 20 tons of lifting force.



ASME B30.1



- Retracted height of just 63,5 mm for the smallest jack and 130,2 mm for the 20 ton, allows you to slip this jack into the narrowest of crevices.
- Jacks operate either horizontally or vertically. Handles function in line with base for easier use in confined spaces.
- The perfect addition to any toolbox, this remarkable little jack has multiple uses that are limited only by your imagination. Use it as a jack or a spreader. Use it to turn your mechanical gear puller (puller capacity must match jack capacity) into a hydraulic puller. Use it vertically or horizontally in limited clearance.

### ORDERING INFORMATION

Cap. Tons	Stroke (mm)	Order Number	Retracted Height Min. (mm)	Max Height (mm)	No. Pump Strokes to Ext. Piston 25 mm	Saddle Dia. (mm)	Base Size Dia. (mm)	Pump Handle Length (mm)	Handle Effort at Rated Cap. (kg)	Carry Handle	Metric tons at 700 bar	Product Weight (kg)
5	19	<b>9105A</b>	63,5	85,7	30	29	73,8	240	26	No	4,5	1,9
5	38	<b>9205A</b>	88,9	130,2	38	29	73,8	240	26	No	4,5	2,4
10	30	<b>9210A</b>	120,7	149,2	36	42,1	109,9	440	28	No	9,1	5,5
20	30	<b>9220A</b>	130,2	160,3	46	52,8	119,9	605	35	No	18,1	8,0

JACKS